Description

Method and switching arrangement for the identification
of Pupin coils

5

The invention relates to a method and a switching
arrangement for the identification of Pupin coils in a
telecommunications line in accordance with the preamble
of Claims 1 and 9, respectively.

10

In order to increase the range when making telephone
calls, earlier it has been the case that occasionally
inductances (so-called Pupin coils or load coils) have
been connected into the subscriber connection line at
15 regular distances. Within the telephone bandwidth up to
about 3.5 kHz, said inductances effect a lower
attenuation and thus an increase in the range or an
improvement in the transmission quality when making
telephone calls.

20

For the frequency range above about 3.5 kHz, the
attenuation rises greatly, however, so that such
connection lines are not suitable for a DSL connection
technology (e.g. ISDN, SDSL, ADSL, VDSL). Only if it is
25 ensured that a connection line is free of Pupin coils
can said line be converted to a DSL transmission
technology.

A decision as to whether a line contains a Pupin coil
30 may be made either by evaluation of installation
documents that are possibly present or by corresponding
measurements. In the case of measurements, a distinction
is made between single-ended and two-ended measuring
arrangements. In the case of two-ended measuring
35 arrangements, the presence of Pupin coils can be deduced
very precisely by measurement of the frequency-dependent

line attenuation. However, such measuring arrangements are not particularly well suited to practical use since both the line end on the switching side and the line end on the subscriber side have to be connected to the

5　measuring arrangement.

In the case of a single-ended measuring arrangement, the presence of a Pupin coil can be identified by measurement of the input resistance within the telephone

10　bandwidth up to about 4 kHz. A magnitude of the input resistance that falls monotonically with the frequency is obtained in the case of a line not connected with Pupin coils. It amounts to less than 1500 Ω at 3.5 kHz. Depending on the line length and the line parameters,

15　the input resistance may also amount to only about 400 Ω. In the case of being connected up with Pupin coils, a profile with a plurality of local maxima results for the input resistance in the frequency range below 4 kHz, the number of local maxima depending on the

20　number of Pupin coils. The absolute maximum is at about 3 to 4 kHz and amounts to more than 3000 Ω. By measuring the input resistance in the frequency range between 3 and 4 kHz, it is thus possible to ascertain whether Pupin coils are present. The input resistance has to be

25　measured directly at the line input. However, the line is connected up to a DSL transceiver always via a transformer and a hybrid arrangement (two-wire – four-wire conversion). The transformer alters the frequency-dependent profile of the input resistance, i.e. of the

30　transformer line, in such a way that a Pupin coil that is possibly present can no longer be identified simply and reliably in this simple manner.

It is an object of the invention to specify a method and

35　also a corresponding circuit arrangement for the identification of Pupin coils.

This object is achieved according to the invention by means of the method according to Claim 1 and the circuit arrangement for the identification of Pupin coils according to Claim 9. The subclaims relate to preferred embodiments of the invention.

The method according to the invention is based on using not the input resistance but the echo transfer function for the identification of the Pupin coils (load coils).

The method according to the invention for the identification of Pupin coil [sic] interposed in a subscriber connection line accordingly comprises the following steps: transmission of periodic transmission symbols by a transmission device, reception, sampling and further processing of an analog reception signal by a reception device, determination of the frequency response of the reception signal for a prescribed number of frequency points in a prescribed frequency range, calculation of a function with function values from the real part and the imaginary part of the frequency response of the reception signal, and determination of a differential vector from the function values by a computing unit, a criterion which specifies whether a pupinized line is present being derived from the components of the differential vector.

In a preferred embodiment of the method, a first partial vector and a second partial vector are formed from the function values by a function generator, an intermediate vector is determined from the second partial vector by a matrix multiplication device and the differential vector is formed from the first partial vector and the intermediate vector in a differential stage. Preferably, in this case, the first partial vector comprises, as

components, the function values with an even-numbered
index and the second partial vector comprises, as
components, the function values with an odd-numbered
index.

5

Preferably, the criterion consists in the difference
between a maximum value and a minimum value of the
components of the differential vector being compared
with a differential prescribed value in a comparator
10   device, and a signal being output if the difference is
greater than the differential prescribed value, or in
the sum of the absolute values of the components of the
differential vector being compared with a sum prescribed
value in a comparator device, and a signal being output
15   if the sum is greater than the sum prescribed value, or
in the sum of the squares of the components of the
differential vector being compared with a square sum
prescribed value in a comparator device, and a signal
being output if the sum is greater than the square sum
20   prescribed value, or in the number of components of the
differential vector which are significantly different
from zero being compared with a zero component
prescribed value in a comparator device, and a signal
being output if the sum is greater than the zero
25   component prescribed value.

In order, in the last case, to be able to determine the
number of components of the differential vector which
are significantly different from zero, the coefficients
30   are rounded and represented with a finite word length,
the quantization size (word length) being chosen such
that the values zero result for all the coefficients in
the case of a non-pupinized line.

35   The preferred prescribed frequency range lies between
about 1 and 5 kHz.

The device for the method for the identification of Pupin coil [sic] interposed in a subscriber connection line is provided with a transmission device for the transmission of periodic transmission symbols, a reception device for the reception, sampling and further processing of an analog reception signal, and a computing unit for determining the frequency response of the reception signal for a prescribed number of frequency points in a prescribed frequency range, calculating a function with function values from the real part and the imaginary part of the frequency response of the reception signal, and determining a differential vector from the function values, a criterion which specifies whether a pupinized line is present being derived from the components of the differential vector.

One advantage of the invention consists, inter alia, in the fact that the measurement of the echo transfer function requires the processing of exclusively the reception signal which is sampled in the DSL receiver when special test signals are transmitted. The method is therefore suitable particularly in the case of being connected up to a DSL transformer and a corresponding hybrid arrangement and can be integrated in a DSL transceiver.

Further features and advantages of the invention emerge from the following description of exemplary embodiments, in which reference is made to the accompanying drawings.

Figure 1 shows the block diagram of a transceiver known per se.

Figure 2 shows the line configuration of a pupinized line.

Figure 3 shows a profile of $F(f)$ for different line configurations.

Figure 4 shows a profile of $\Delta F(f)$ for different line configurations

Figure 5 shows the profile of the frequency response of $\Delta r(f_i)$ for different line configurations.

Figure 6 shows the profile of the real and imaginary parts of the frequency response of $\Delta r(f_i)$ for different line configurations.

Figure 7 shows a first embodiment of the circuit arrangement according to the invention for the identification of Pupin coils.

Figure 8 shows a second embodiment of the circuit arrangement according to the invention for the identification of Pupin coils.

Figure 1 shows the block diagram of a digital transceiver 1 known per se, having a digital transmitter 2, a digital receiver 3, a D/A converter 4 at the transmitter end and an A/D converter 6 at the receiver end, a line amplifier (line driver) 5 and also a line connection (hybrid) 7. A transmission line 9 is connected to the line connection 7 via a line transformer 8.

The subscriber connection line 9 is either a non-pupinized line (without Pupin coils) or a pupinized line (with Pupin coils).

A simple nomenclature is used in the USA for the description of the Pupin line. Lines bearing the designation D66 and H88 are found the most often. The inductance of the Pupin coil is 66 mH in the case of the D66 line, and 88 mH in the case of the H88 line. The distance between two coils is 1356 m and 1829 m (4450 ft and 6000 ft), respectively. In this case, the D66 line has a limiting frequency of about 3.4 kHz and the H88 line has a limiting frequency of about 4 kHz.

The line configuration of a pupinized line is shown in Figure 2. The illustration shows a connection line 9 with inductances 10, in which case the line 9 may be a D66 line or an H88 line, i.e. the length L between two adjacent inductances 10 is 1356 m in the case of the D66 line and 1829 m in the case of the H88 line.

In order to identify whether the connected transmission line contains Pupin coils, the transfer function is evaluated for different frequencies. In this case, the term transfer function denotes the ratio of reception signal to transmission signal when a sinusoidal signal having a specific frequency is transmitted.

The determination of the transfer function is explained below.

The intention is to determine the transfer function at the frequency f_o. For this purpose, a baud rate f_T of

$$f_T = N \cdot f_0,$$

where N is even (e.g. N = 32),
is chosen for the transceiver.

A periodic data sequence with $\frac{N}{2}$ positive and $\frac{N}{2}$ negative symbols each having the same amplitude is then transmitted. Consequently, the transmission signal also contains odd-numbered harmonics in addition to the

5   fundamental with the frequency f_o.

In order to determine the transfer function at the frequency f_o, the fundamental has to be filtered out of the reception signal. For this purpose, the signal

10   sampled at the baud rate (symbol rate) f_T is multiplied on the one hand by the cosine of the fundamental and on the other hand by the sine of the fundamental. The following two signals are then obtained:

15   $$y_1(k) \; = \; y(k) \cdot \cos\left(2 \cdot \pi \cdot \frac{k}{N}\right)$$

and

$$y_2(k) \; = \; y(k) \cdot \sin\left(2 \cdot \pi \cdot \frac{k}{N}\right)$$

20

where k = 1 to N.

The real part and the imaginary part of the transfer function are obtained from the arithmetic mean of the

25   two signal sequences, it being necessary to effect averaging over an integer number M of signal periods.

The real part and the imaginary part of the frequency response can thus be determined using the following

30   relationships:

$$\text{Re}\{H(f_o)\} \; = \; \frac{2}{N \cdot M} \sum_{k=1}^{N \cdot M} y_1(k)$$

and

$$\text{Im}\{H(f_0)\} \;=\; \frac{2}{N \cdot M} \sum_{k=1}^{N \cdot M} y_2(k) \,.$$

5   In order to measure the frequency response, it is
necessary to determine the real part and the imaginary
part for different further frequencies f in addition to
f_0 by corresponding alteration of the baud rate (symbol
rate) f_T.

10

For the detection of Pupin coils, both the real part and
the imaginary part

$a(f)\;=\;\text{Re}\{H(f)\}$

15

and

$b(f)\;=\;\text{Im}\{H(f)\}$

20   of the frequency response are processed further.

Firstly, a suitable function for the further processing
is formed from a and b. This function may be e.g. the
square of the magnitude $F(f)=a(f)^2+b(f)^2$ formed from real
25   and imaginary parts, the magnitude $F(f)=\sqrt{a(f)^2+b(f)^2}$
formed from real and imaginary parts, the sum
$F(f)=a(f)+b(f)$ from real and imaginary parts, the
difference $F(f)=a(f)-b(f)$ formed from real and imaginary
parts or the product $F(f)=a(f)\cdot b(f)$ formed from real and
30   imaginary parts.

In the case of a line without Pupin coils, a largely
smooth profile which is frequency-dependent is obtained
for the function F derived from a and b, while a line

with Pupin coils results in a slightly "wavy" profile in the frequency range of about 2 kHz to 4 kHz.

The profile of F is illustrated in Figure 3. In
5   Figure 3, the square of the magnitude of the frequency response $F(f) = a(f)^2 + b(f)^2$ was used as the function for the further processing.

Three different curve [sic], designated by "1", "2" and
10 "3", are plotted in Figure 3. Curve "1" corresponds to a line having a thickness of 0.4 mm and a length of 7.3 km. It does not have a Pupin coil in the example shown. Curve "2" corresponds to a line having a thickness of 0.4 mm and a length of 7.3 km. It has four
15 Pupin coils in the H88 arrangement in the example shown. Curve "3" corresponds to a line having a thickness of 0.4 mm and a length of 1.83 km. It does not have a Pupin coil in the example shown.

20 Only support points of the function used at some frequency points in the range of about 1 kHz to about 5 kHz are selected for the further processing. A corresponding reference function $F(f)$ is calculated from these support values. The reference function represents
25 a power function of the frequency and approximates the originally measured function in the sense of the least square deviation:

$$F(f) = \sum_{i=0}^{n} \alpha_i \cdot f^i .$$

30

The coefficients α_i are calculated from the support values of the function $F(f)$ which are measured at the frequency values f.

While the reference function $F(f)$ corresponds to the derived function very well in the case of a line without a Pupin coil, an approximation with a power function is possible only with large deviations in the case of a
5   line with Pupin coils.

The difference between the original function and the reference function is now used to identify Pupin coils.

10   Figure 4 shows the respective differential function of the examples used in Figure 3 for the profile. The parameters of the curves "1", "2" and "3" are the same as in Figure 3. The coefficients α_i were calculated from in each case eight support values in the range of 1.9 to
15   4.5 Hz.

The method for calculating the α_i and the determination of the reference function therefrom are described in more detail below.
20

m frequency points f_i where $i = 1$ to m are considered. These are used to form the rectangular matrix Q with the coefficients

25   $$Q_{i,j} = f_i^{\,j-1}$$

where $i = 1$ to m and $j = 1$ to n+1. The following rectangular matrix then results e.g. for n = 4 and m = 8:

30

$$Q = \begin{bmatrix} 1 & f_1 & f_1^2 & f_1^3 & f_1^4 \\ 1 & f_2 & f_2^2 & f_2^3 & f_2^4 \\ 1 & f_3 & f_3^2 & f_3^3 & f_3^4 \\ 1 & f_4 & f_4^2 & f_4^3 & f_4^4 \\ 1 & f_5 & f_5^2 & f_5^3 & f_5^4 \\ 1 & f_6 & f_6^2 & f_6^3 & f_6^4 \\ 1 & f_7 & f_7^2 & f_7^3 & f_7^4 \\ 1 & f_8 & f_8^2 & f_8^3 & f_8^4 \end{bmatrix} .$$

A vector r with the components

5     $r_i = F(f_i)$

is formed from m values of the function $F(f)$ to be evaluated.

10   An explanation is given below of two alternatives in the evaluation of the vector r in order to determine a differential vector for the further evaluation of the measurement.

15   In the case of a first evaluation method, for m = 8, the vector r can be represented as follows:

$$r = \begin{bmatrix} F(f_1) \\ F(f_2) \\ F(f_3) \\ F(f_4) \\ F(f_5) \\ F(f_6) \\ F(f_7) \\ F(f_8) \end{bmatrix} .$$

20   The vector r is used to obtain a coefficient vector α with the coefficients α_i according to the relationship

$$\alpha = (Q^T \cdot Q)^{-1} \cdot Q^T \cdot r.$$

In this case, the superscript T denotes the transposition operation.

With

$$R = (Q^T \cdot Q)^{-1} \cdot Q^T$$

this can be summarized as:

$$\alpha = R \cdot r.$$

The rectangular matrix R is dependent only on the frequency support values and the vector r is dependent only on the support values of the function $F(f_i)$ to be evaluated.

The differential function is likewise evaluated only using the support values with which the coefficient vector was calculated.

With the coefficient vector α, the following is obtained for the reference vector

$$r_{ref} = Q \cdot \alpha,$$

and the following results for the differential vector

$$\Delta r = r - r_{ref} = r - Q \cdot \alpha = r - Q \cdot R \cdot r = [E - Q \cdot R] \cdot r \ ,$$

where the matrix E is an (m × m) unit matrix.

If the following is written for the matrix

$$P = [E - Q \cdot R] \, ,$$

the differential vector can be represented as

5      $\Delta r = P \cdot r \, .$

In this case, P is a square, symmetrical (m × m) matrix which depends only on the frequency support points. The vector r directly contains the support values of the
10   function which is to be evaluated and is obtained by corresponding combination from the measured real and imaginary parts of the transfer function. Accordingly, each value of the differential vector is obtained by multiplying a row vector by a column vector.
15

An alternative approach is specified below, which permits a more rapid calculation in order to determine the differential vector.

20   In the case of this second approach, the original vector r is divided into two partial vectors $r1$ and $r2$, in which case, by way of example, the vector $r1$ contains the components of r with the odd frequency numbers and the vector $r2$ contains the components of r with the even
25   frequency numbers.

The vector $r2$ can be used to calculate the unknown coefficients of the vector α according to

30    $\alpha = (Q_2{}^T \cdot Q_2)^{-1} \cdot Q_2{}^T \cdot r2 = R2 \cdot r2 \, ,$

where the matrices Q_2 and $R2$ in each case result from the same frequency support values as $r2$ (e.g. the even frequency support values).
35

The reference vector is only calculated for the frequency support values which correspond to the vector $r1$. The following is obtained for said reference vector

5      $rl_{ref} = Q_1 \cdot \alpha = Q_1 \cdot R2 \cdot r2$.

In this case, the matrix Q_1 results from the frequency support values which were taken as a basis for determining the vector $r1$.

10

The differential vector is then

$\Delta r1 = r1 - rl_{ref} = r1 - Q_1 \cdot R2 \cdot r2$.

15   With

$P12 = Q_1 \cdot R2$

the following is obtained therefrom

20

$\Delta r1 = r1 - P12 \cdot r2$.

The differential vector $\Delta r1$ thus results from the difference between the vector $r1$ and a vector which
25   results from the product of a square matrix $P12$ and the vector $r2$. In this case, in the above example, $r1$ is determined from the odd frequency support values and $r2$ is determined from the even frequency support values.

30   The realization outlay is lower in the case of the second embodiment than in the case of the first embodiment for determining the differential vector, since the matrix multiplication is carried out with a lower number of coefficients.

35

The differential vectors are shown in Figure 5. The parameters of curves "1", "2" and "3" are the same as in Figure 3 and Figure 4, respectively.

5   The values correspond to the differential functions from Figure 4 if, for the frequencies, use is made of the support values thereof. For calculation purposes, the support values of the transfer function values determined from the frequency response values were taken

10   as a basis with the accuracy of the computer. Since the frequency response values are determined by measurement, a finite accuracy must inevitably be expected for $a(f)$ and $b(f)$. The differential vectors determined with a finite accuracy of the real part $a(f)$ and of the

15   imaginary part $b(f)$ of 10 bits are illustrated in Figure 6. The parameters of curves "1", "2" and "3" are the same as in Figure 3, Figure 4 and Figure 5, respectively. Although the values of the differential vector increase for the non-pupinized lines, they are

20   still significantly less than for the pupinized line. The presence of Pupin coils can thus be deduced by suitable evaluation of the differential vector.

An explanation is given below of the possibilities for

25   evaluating the differential function or the differential vector in order to arrive at a criterion for the decision as to whether a Pupin coil is present in the line examined - independently of its configuration as a D66 or H88 line.

30

As can be gathered from Figures 5 and 6, non-pupinized lines result in differential vectors whose components are smaller than in the case of pupinized lines. The differential vector can therefore be used to identify

35   Pupin coils. It is necessary firstly to derive a criterion, it being possible for the actual

identification to be effected by comparing said
criterion with a threshold value that is to be chosen in
a suitable manner.

5   Possible criteria are 1) the difference between the
maximum value and the minimum value of the components of
the differential vector, i.e. $criterion = \Delta r_{max} - \Delta r_{min}$, 2) the
sum of the absolute values of the components of the
differential vector, i.e. $criterion = \sum_i \Delta|r_i|$, or 3) the sum of

10   the squares of the components of the differential
vector, i.e. $criterion = \sum_i \Delta r_i^2$. 4) the number of components

which are different from zero may be defined as a
further criterion. For this purpose, the coefficients
are firstly rounded and represented with a finite word

15   length. The quantization size (word length) is chosen
such that the values zero result for all the
coefficients in the case of a non-pupinized line. In the
above example, the word length chosen may be 9 bits, for
example, and the quantization level is thus 2^{-8}.

20

The criteria 1) to 4) mentioned as an example do not
have to be checked directly after the determination of
the differential vector; the differential vector may
still be modified beforehand in order that the checking

25   of one of the criteria 1) to 4) is simplified, for
example. One possible modification consists e.g. in
forming the difference between two adjacent vector
components:

30   $d\Delta r_i = \Delta r_i - \Delta r_{i-1}$

or in forming the difference in the difference between
two adjacent vector components:

35   $dd\Delta r_i = d\Delta r_i - d\Delta r_{i-1}$.

The method for the identification of Pupin coils may be
implemented using the circuit arrangement illustrated in
Figure 7. This resorts to the first method for
5   calculating the differential vector. Elements identical
to those in Figure 1 have the same reference symbols as
there. The construction of Figure 7 differs from that in
Figure 1 by the fact that a frequency response measuring
device 11 periodically outputs transmission symbols to
10   the transmitter 2, which are transmitted by the
transmitter 2 on the subscriber connection line 9. At
the same time, the frequency response measuring device
11 outputs the symbol clock to the transmitter 2, the
receiver 3 and the A/D converter 6 connected upstream of
15   the latter.

The received analog echo signal is tapped off between
the AD converter 6 and the receiver 3 and sampled in the
frequency response measuring device 11 in order to
20   generate the components $a(f)$ and $b(f)$ (more precisely the
support values $a(f_i)$ and $b(f_i)$) for a specific number of
frequency points in the range of about 1 to 5 kHz. The
components $a(f)$ and $b(f)$ are the real part and the
imaginary part, respectively, of a function $F(f_i)$ which
25   is calculated in a function generator 12.

The function generator 12 outputs the output values r_i to
a matrix multiplication device 13, which determines a
differential vector from said values with the aid of a
30   matrix multiplication. For this purpose, as described
above, the output values r_i are multiplied by a matrix
$P = [E - Q \cdot R]$, thereby producing the values Δr_i, which are
input variables of a comparator device 14.

35   In the comparator device 14, a suitable criterion
derived from the coefficients of the differential vector

is used to make a reliable statement as to whether or not a pupinized line is present.

A second embodiment of the circuit arrangement according to the invention for the identification of Pupin coils is shown in Figure 8. In this embodiment, the differential vector is calculated according to the alternative, second method. Elements identical to those in Figures 1 and 7 have the same reference symbols as there. The construction of Figure 8 differs from that in Figure 7 by the fact that the output values $r1_i$ and $r2_i$ are formed by the function generator 12. In this case, by way of example, the components with an even-numbered index form a first partial vector $r1$ and the components with an odd-numbered index form a second partial vector $r2$. The partial vector $r1$ with the components $r1_i$ is output directly to a differential stage 15, while the partial vector $r2$ with the components $r2_i$ forms the input variable of the matrix multiplication device 13, which determines an intermediate vector $P12 \cdot r2$ from the values $r2_i$ with the aid of a matrix multiplication. Said intermediate vector is subtracted from the partial vector $r1$ in the differential stage 15, thereby producing the differential vector with the components Δr_i, which are input variables of the comparator device 14.

The method is then brought to an end analogously to the device in Figure 7.

The measuring method can be integrated in a simple manner in a DSL transceiver. The subsystems such as transmitter and A/D converter which are required for the measurement of the frequency response are present anyway, so that they do not incur any additional outlay. The signal processing required for the evaluation can be

carried out with the aid of a processor which is quite generally likewise present, it being necessary merely to extend the firmware of the transceiver for this purpose.